

The background of the entire page is a photograph of a large iceberg floating in the ocean. The iceberg is white and jagged, with a large, dark shadow cast on the water to its right. The sky is a pale blue with some light clouds. The water is a deep blue. The overall tone is cool and refreshing, fitting the theme of water coolers.

CATALOG **WATER COOLERS**

- 2** Technical Guide
- 2** Table top
- 4** Undercounter
- 7** Free standing & table top
- 8** Free standing
- 9** Accessories



 CAPACITY	COOLING SYSTEM	
 TEMPERATURE ADJUSTMENT DIGITAL	 TEMPERATURE ADJUSTMENT MECHANICS	
 AMBIENT WATER	 COLD SPARKLING WATER	
 HOT WATER	 COLD WATER	
 COOLING SYSTEM INSTANT	 COOLING SYSTEM ICE BANK	
 KIT INSTALLATION	 REVERSE OSMOSIS SYSTEM	
 WATER STOP SYSTEM	Prevents water leakage by blocking the system.	
 DUPLEX DISPENSE NOZZLE	Prevents contamination - customers fingers and hands can never come into direct contact with the point of water dispense.	
 ELECTRONIC CONTROL UNIT	Control of every operation phase, to ensure absolute safety and to protect your health.	
 SISTEMA HPDC®	Il sistema esclusivo HPDC®, eroga acqua fredda in meno di 3 minuti con una potenza frigorifera di 450Kcal/h, una capacità di erogazione di 60 l/h e un risparmio energetico del 70%.	
 DRIP TRAY	Drips from the dispense nozzle are collected in the removable drip tray, when the drip tray is full a red float display will appear to indicate to the customer to empty it. Also the drip tray has been designed with permanent drain facility in mind so you can permanently drain the drip tray if required. Large Dispense space to accommodate for sport bottles and jugs to fit under with ease.	
 SILVER TURBO CLEAN SYSTEM	Improve the heat exchange mechanism and hygiene levels in products with refrigeration chambers. Liquid enters via nozzles, creating a vortex around the refrigeration chamber walls, which increases the efficiency of the heat exchange and also eliminates the possibility of stagnation. Water oxidizes the silver particles releasing ions which carry out a proved bactericidal action.	
 DIGITAL EYE	A sophisticated microprocessor-based control and management system. The main operating functions can be automated by using the digital display: beverage dispensing temperature programming and readouts, and set-up of the two most used container sizes; for example, cups and carafes, with user specified capacities. In addition, the control system monitors the conditions of filter elements and let you know when standard maintenance is required. The system can also stop the supply of water when the filters have not been replaced, avoiding any potentially dangerous situations arising.	

WATER COOLERS Table top

AQUAIS 80, 90

Table top 2/3-way



CONNECTIONS: 2-way

Water inlet: DMfit Bulkhead 1/4" male

CONNECTIONS: 3-way

Water inlet: DMfit Bulkhead 1/4" quick fit

Co2 inlet: DMfit Bulkhead 1/4" quick fit

FEATURES

Power supply	220-230V / 50Hz - Schuko European plug
Dispensed products 2-way	Aquais 80
Dispensed products 3-way	Aquais 90
Power consumption	110 W
Water inlet Pressure / CO ²	min. 2.5 bar - max 5 bar / pressure CO ² 0 - 5 bar
Compressor	1/15 hp
Cooling system	Silver turbo clean Ice bank
Cooling capacity	(ambient temp - lt./h.) 32°C. - 6lt./h. ~ 18°C. - 19 lt./h.
Temperature adjustment	Mechanical
Connection to the water mains	Yes
Water and refrigerant GAS tubes	Antibacterials
Carbonator capacity	1,4 lt. (Aquais 90)
Membrane carbonator pump	75 lt./h
Rotary carbonator pump	-
Dimensions (LxPxH, mm)	240 x 470 x 380

AQUAIS 80, 90

Table top 2/3-way



CONNECTIONS: 2-way

Water inlet: DMfit Bulkhead 1/4" male

CONNECTIONS: 3-way

Water inlet: DMfit Bulkhead 1/4" quick fit

Co2 inlet: DMfit Bulkhead 1/4" quick fit

220-230V / 50Hz - Schuko European plug

Aquais 80

Aquais 90

110 W

min. 2.5 bar - max 5 bar / pressure CO² 0 - 5 bar

1/15 hp

Silver turbo clean Ice bank

(ambient temp - lt./h.) 32°C. - 6lt./h. ~ 18°C. - 19 lt./h.

Mechanical

Yes

Antibacterials

1,4 lt. (Aquais 90)

75 lt./h

-

240 x 470 x 380

WATER COOLERS

Table top

TIVOLI 270 PLEX

Table top 3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 1/4" quick fit
Co2 inlet: DMfit Bulkhead 1/4" quick fit

FEATURES

Power supply	220-230V / 50Hz - Schuko European plug
Dispensed products 2-way	-
Dispensed products 3-way	Yes
Power consumption	155 W
Water inlet Pressure / CO ²	min. 2.5 bar - max 5 bar / pressure CO ² 0 - 5 bar
Compressor	1/6 hp
Cooling system	Silver turbo clean Ice bank
Cooling capacity	(ambient temp - lt./h.) 32°C. - 14 lt./h. ~ 18°C. - 28 lt./h.
Temperature adjustment	Digital
Connection to the water mains	Yes
Water and refrigerant GAS tubes	Antibacterials
Carbonator capacity	1,4 lt.
Membrane carbonator pump	230 lt./h
Rotary carbonator pump	-
Dimensions (LxPxH, mm)	235 x 435 x 400

POLARES INOX

Table top 2/3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 8 mm quick fit
Co2 inlet: DMfit Bulkhead 6 mm quick fit
Water outlet: DMfit Bulkhead 8 mm quick fit

220/230V - 50Hz - Schuko European plug

Yes
Yes
280 W
min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar
1/8 hp
Ice bank
60 lt./h
Mechanical
Yes
-
1 lt.
-
200 Lt/h (nom.)
294 x 385 x 435 / Drip trays (315 x 165 x 25)

POLARES INOX

Table top 2/3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 8 mm quick fit
Co2 inlet: DMfit Bulkhead 6 mm quick fit
Water outlet: DMfit Bulkhead 8 mm quick fit

220/230V - 50Hz - Schuko European plug

Yes
Yes
350 W
min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar
1/5 hp
Ice bank
90 lt./h
Mechanical
Yes
-
1,27 lt.
-
200 Lt/h (nom.)
360 x 420 x 440 / Drip trays (315 x 165 x 25)

POLARES INOX

Table top 3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 8 mm quick fit
Co2 inlet: DMfit Bulkhead 6 mm quick fit
Water outlet: DMfit Bulkhead 8 mm quick fit

20/230V - 50Hz - Schuko European plug

-
Yes
350 W
min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar
1/5 hp
Ice bank
120 lt./h
Mechanical
Yes
-
1,5 lt
-
300 Lt/h (nom.)
360 x 513 x 440 / Drip trays (315 x 165 x 25)

WATER COOLERS Undercounter

REFRESH® U 80/90

Undercounter 2/3-way



CONNECTIONS: 20030030-004

Water inlet: DMfit Bulkhead 5/16" quick fit.

Water outlet: DMfit Bulkhead 5/16" quick fit

CONNECTIONS: 20030030-002

Water inlet: DMfit Bulkhead 1/4" quick fit

Co2 inlet: DMfit Bulkhead 1/4" quick fit

Water outlet: DMfit Bulkhead 1/4" quick fit

FEATURES

Power supply	220-230V / 50Hz - Schuko European plug
Dispensed products 2-way	REFRESH U 80
Dispensed products 3-way	REFRESH U 90
Power consumption	85 W (REFRESH U 80) - 110 W (REFRESH U 90)
Water inlet Pressure / CO ²	min. 2,5 bar - max 5 bar / pressure CO ² 0 - 5 bar
Compressor	1/15 hp
Cooling system	Silver turbo clean Ice bank
Cooling capacity	(ambient temp. - lt./h.) 32°C. - 6 lt./h. ~ 18°C. - 19 lt./h.
Temperature adjustment	Mechanical
Connection to the water mains	Yes
Water and refrigerant GAS tubes	Antibacterials
Carbonator capacity	1,4 lt (REFRESH U 90)
Membrane carbonator pump	75 lt./h
Rotary carbonator pump	-
Water recirculation pump	-
Dimensions (LxPxH, mm)	240 x 325 x 385

REFRESH® U 270

Undercounter 3-way



CONNECTIONS:

Water inlet: DMfit Elbow union 5/16" quick fit

Co2 inlet: DMfit Elbow union 5/16" quick fit

Water outlet: DMfit Elbow union 5/16" quick fit

220-230V / 50Hz - Schuko European plug

-
Yes
115 W
min. 2,5 bar - max 5 bar / pressure CO ² 0 - 5 bar
1/6 hp
Silver turbo clean Ice bank
(ambient temp. - lt./h.) 32°C. - 6 lt./h. ~ 18°C. - 19 lt./h.
Mechanical
Yes
Antibacterials
1,4 lt
230 lt./h
-
-
240 x 325 x 385

SODABAR

Undercounter 3-way



CONNECTIONS:

Water inlet: DMfit Straight Adaptor 3/8" quick fit

Co2 inlet: DMfit Bulkhead 1/4" quick fit

Water outlet: DMfit Bulkhead 1/4" quick fit

220-230V / 50Hz - Schuko European plug

-
Yes
270W
min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar
1/8 hp
Instant
25 lt./h (recovery 1,5min.)
Digital
Yes
Antibacterials
1lt.
80 lt./h
-
8mt. max. (maintains the cold water in the whole line)
194 x 474 x 353

SODABAR R.O.

Undercounter 3-way



CONNECTIONS:

Water inlet: DMfit Straight Adaptor 3/8" quick fit

Co2 inlet: DMfit Bulkhead 1/4" quick fit

Water outlet: DMfit Bulkhead 1/4" quick fit

220-230V / 50Hz - Schuko European plug

-
Yes
270W
min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar
1/8 hp
Instant
25 lt./h (recovery 1,5min.)
Digital
Yes
Antibacterials
1 lt.
-
300 lt./h (nom.)
8mt. max. (maintains the cold water in the whole line)
285 x 474 x 353

WATER COOLERS Undercounter

SONLINE

Undercounter 3-way



CONNECTIONS:

Water inlet: Dmfit Straight Adaptor 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 6mm quick fit

FEATURES

Power supply	220/230V - 50Hz - Standard European Plug
Dispensed products 2-way	-
Dispensed products 3-way	Yes
Power consumption	280W
Water inlet Pressure / CO ²	min. 1,5 bar - max 3 bar / pressure CO ² 0 - 5 bar
Compressor	1/8 hp
Cooling system	Ice bank
Cooling capacity	lt./h
Temperature adjustment	Mechanical
Connection to the water mains	Yes
Water and refrigerant GAS tubes	-
Carbonator capacity	5 lt.
Membrane carbonator pump	-
Rotary carbonator pump	200 lt./h (nom.)
Water recirculation pump	-
Dimensions (LxPxH, mm)	294 x 384 x 433

SONLINE

Undercounter 3-way



CONNECTIONS:

Water inlet: Dmfit Straight Adaptor 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 6mm quick fit

220/230V - 50Hz - Standard European Plug

Power supply	220/230V - 50Hz - Standard European Plug
Dispensed products 2-way	-
Dispensed products 3-way	Yes
Power consumption	280W
Water inlet Pressure / CO ²	min. 1,5 bar - max 3 bar / pressure CO ² 0 - 5 bar
Compressor	1/8 hp
Cooling system	Ice bank
Cooling capacity	lt./h
Temperature adjustment	Mechanical
Connection to the water mains	Yes
Water and refrigerant GAS tubes	-
Carbonator capacity	5 lt.
Membrane carbonator pump	-
Rotary carbonator pump	200 lt./h (nom.)
Water recirculation pump	-
Dimensions (LxPxH, mm)	294 x 384 x 433

SONLINE

Undercounter 2-way



CONNECTIONS:

Water inlet: Dmfit Straight Adaptor 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 6mm quick fit

220/230V - 50Hz - Standard European Plug

Power supply	220/230V - 50Hz - Standard European Plug
Dispensed products 2-way	Yes
Dispensed products 3-way	-
Power consumption	280W
Water inlet Pressure / CO ²	min. 1,5 bar - max 3 bar / pressure CO ² 0 - 5 bar
Compressor	1/8 hp
Cooling system	Ice bank
Cooling capacity	lt./h
Temperature adjustment	Mechanical
Connection to the water mains	Yes
Water and refrigerant GAS tubes	-
Carbonator capacity	5 lt.
Membrane carbonator pump	-
Rotary carbonator pump	200 lt./h (nom.)
Water recirculation pump	-
Dimensions (LxPxH, mm)	294 x 384 x 433

POLARES INOX

Undercounter 3-way



CONNECTIONS:

Water inlet: Dmfit Bulkhead 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 6mm quick fit
Cooling water outlet: DMfit Bulkhead 6mm quick fit

220/230V - 50Hz - Standard European Plug

Power supply	220/230V - 50Hz - Standard European Plug
Dispensed products 2-way	-
Dispensed products 3-way	Yes
Power consumption	230W
Water inlet Pressure / CO ²	min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar
Compressor	1/8 hp
Cooling system	Ice bank
Cooling capacity	30 lt./h
Temperature adjustment	Mechanical
Connection to the water mains	Yes
Water and refrigerant GAS tubes	-
Carbonator capacity	0,63 lt.
Membrane carbonator pump	-
Rotary carbonator pump	200 lt./h (nom.)
Water recirculation pump	-
Dimensions (LxPxH, mm)	170 x 335 x 440

WATER COOLERS Undercounter

POLARES INOX

Undercounter 2/3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 8mm quick fit

POLARES INOX

Undercounter 2/3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 8mm quick fit

POLARES INOX

Undercounter 3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 8mm quick fit
Water recirculation outlet: DMfit 8mm quick fit

POLARES INOX

Undercounter 3-way



CONNECTIONS:

Water inlet: DMfit Bulkhead 8mm quick fit
Co2 inlet: DMfit Bulkhead 6mm quick fit
Water outlet: DMfit Bulkhead 8mm quick fit
Water recirculation outlet: DMfit 8mm quick fit

FEATURES

Power supply	220/230V - 50Hz - Standard European Plug	220/230V - 50Hz - Standard European Plug	220/230V - 50Hz - Standard European Plug	220/230V - 50Hz - Standard European Plug
Dispensed products 2-way	Yes	Yes	-	-
Dispensed products 3-way	Yes	Yes	Yes	Yes
Power consumption	280W	350W	350 / 410W	350 / 410W
Water inlet Pressure / CO ²	min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar	min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar	min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar	min. 1 bar - max 4 bar / pressure CO ² 0 - 5 bar
Compressor	1/4 hp	1/5 hp	1/2 hp	1/2 hp
Cooling system	Ice bank	Ice bank	Ice bank	Ice bank
Cooling capacity	60 lt./h	90 lt./h	120 lt./h	150 lt./h
Temperature adjustment	Mechanical	Mechanical	Mechanical	Mechanical
Connection to the water mains	Yes	Yes	Yes	Yes
Water and refrigerant GAS tubes	-	-	-	-
Carbonator capacity	1,3 lt.	1,3 lt.	2 lt.	2 lt.
Membrane carbonator pump	-	-	-	-
Rotary carbonator pump	200 lt./h (nom.)	200 lt./h (nom.)	300 lt./h (nom.)	300 lt./h (nom.)
Water recirculation pump	6mt. max. (maintains the cold water in the whole line)	8mt. max. (maintains the cold water in the whole line)	8mt. max. (maintains the cold water in the whole line)	8mt. max. (maintains the cold water in the whole line)
Dimensions (LxPxH, mm)	294 x 385 x 435	360 x 420 x 440	360 x 513 x 440	360 x 513 x 440

WATER COOLERS

Free standing & table top

FC750

Free standing, table top **2/3-way**



FEATURES

Power supply	220-240V / 50Hz - Schuko European plug
Dispensed products 2-way	Yes
Dispensed products 3-way	Yes (hot water + cold water + R.O.)
Compressor	120 W
Cooling system	Tank
Cooling capacity	5 lt./h
Heating capacity	7 lt./h
Carbonator capacity	-
Temperature adjustment	Digital
Connection to the water mains	Yes
Water and refrigerant GAS tubes	-
Membrane carbonator pump	-
Booster pump	Yes
Dimensions (LxPxH, mm)	Table top (260 x 455 x 490) Free standing (260 x 347 x1100)

CONNECTIONS:

Water inlet: DMfit 8mm. quick fit

FLEET

Free standing, table top **2-way**



220-240V / 50Hz - Schuko European plug

Yes

-

75 W

Ice bank

6 lt./h

9 lt./h

0,40 lt./h (only mod. 20030013-015)

Digital

Yes

-

80 Lt/h (nom.) (only mod. 20030013-015)

-

Table top (365 x 380 x 502) free standing (365 x 350 x1125)

CONNECTIONS:

Water inlet: DMfit 8mm. quick fit

Co2 inlet: DMfit 1/4" quick fit

(only versions with sparkling water)

WATER COOLERS Free standing

FUTURA

Free standing 2/3-way



CONNECTIONS:

Water inlet: DMfit 1/4" bulkhead quick fit.

• To purchase with every systems:

- Disposable Co2 steel cylinder 0,600gr

• Accessories included in the system:

- 3M bayonet fit water filter
- Co2 disposable cylinder pressure reducer

• Filter features:

- Chlorine reduction.
- Bacteriostatic.
- Reduction of cysts.
- Reduction of particulate in suspension.
- Technology: activated carbon
- Micron rating: 0,5 micron
- Service life: 4.000 liters (1.060 gallons)

• Capacity varies according to:

- Inlet water quality
- Required flow rate
- Inlet water pressure
- Filter use (continuous or intermittent)
- Service flow rate: 1,9 l./Min. (0,5 gpm)
- Temperature: 35 - 100°F (2-38°C)
- Pressure: 25 - 125 psi (1,72 - 8,62 bar), non-shock

FEATURES

Power supply	220-240V / 50Hz - Schuko European plug
Dispensed products 1-way	-
Dispensed products 2-way	FUTURA 80
Dispensed products 3-way	FUTURA 81 - FUTURA 90
Power consumption	110 W
Water inlet Pressure / CO ²	min. 2,5 bar - max 5 bar / pressure CO ² 0 - 5 bar
Compressor	1/15 hp
Cooling system	Silver turbo clean Ice bank
Cooling capacity	(ambient temp. - lt./h) 32°C. - 6 lt./h ~18°C.-19 lt./h
Temperature adjustment	Mechanical
Connection to the water mains	Yes
Water and refrigerant GAS tubes	Antibacterials
Carbonator capacity	1,4 lt. (FUTURA 90)
Membrane carbonator pump	75 lt./h (FUTURA 90)
Dimensions (LxPxH, mm)	250 x 175 x 1060



• Activation:

- It is advisable to run water through filter at maximum pressure and full flow rate, for at least 5 minutes to allow air purging and flushing of cartridge.

• Cartridge change:

- When capacity is reached, or when flow comes too slow (precipitates under 0.7bar/10psi), every 6 months but at least annually.

REFRESH® P 240

Free standing 1-way



CONNESSIONI:

Water inlet 20030027-001: DMfit 1/4" female

Water inlet 20030027-002: DMfit 8mm. quick fit

Water inlet 20030027-003: DMfit 1/4" female

Drain line outlet: 20cm. tube from 25mm. OD.



220-230V / 50Hz - Schuko European plug

Yes
-
-
250 W
min. 2,5 bar - max 5 bar
1/6 hp plus
HPDC® instant (recovery 3min.)
(ambient temp. - lt./h) 32°C. - 27 lt./h ~18°C. - 74 lt./h
Mechanical
Yes
Antibacterials
-
-
310 x 305 x 980




WATER COOLERS accessories



Stainless steel cabinet

With convenient access to the compartment cover where you can put inside the Co2 cylinder and filtering system.

Dimensions (LxPxH, mm)
240 x 450 x 880




Washing basket

Material: plastic
Unit: 20
Color: blue and grey
Dimensions: 50 x 50



Washing basket

Material: plastic
Unit: 9
Color: blue and grey
Dimensions: 40 x 40



Washing basket

Material: plastic
Unit: 9
Color: grey
Dimensions: 40 x 40



Sodabar bottle

Glass bottle 85cl.



Cup dispenser

For 100pcs. application with magnet



DM fit Tubing LLDPE

- Inch size
- Metric size



Cabinet

with 2 cup dispenser

With convenient access to the compartment cover with sugar and stirrers; cylinders cupholders have a capacity of 50 cups of coffee for cylinder.

Dimensions (LxPxH, mm)
340 x 350 x 900



Co2 cylinder rechargeable

Cylinder in aluminum or steel: **1Kg, 2Kg, 4Kg, 5Kg, 10Kg, 20Kg, 30Kg**



Disposable CO2 cylinder

E290 for water coolers **600gr.**



Disposable CO2 cylinder

E290 for water coolers **1.300gr.**



SR-02

Co2 pressure reducer for **disposable** cylinder knob to 90°

Connection: 11x1



SR-02 ADV

Co2 pressure reducer for **rechargeable** cylinder (2 gauges)

Connection: 21.8X1/14"



SR-02

Co2 pressure reducer for **rechargeable** cylinder knob straight

Connection: 21.8X1/14"



Cabinet

with 3 cup dispenser

Cabinet support for coffee machines and water coolers for two-color black-metal gray with CE marking.

Holes glasses:
2 Small- 1 Large

Dimensions (LxPxH, mm)
860 x 340 x 425



Bacwater

120cc sanitizing for domestic reverse osmosis



Cooler Clean

Sanitizing sprays for household systems **100ml**



Cooler clean

Dosing device product for the hygienisation of water dispensers **1lt.**



Cooler Clean

Home hygienisation kit for water coolers reverse osmosis



Cooler Clean



Sponge for water coolers **8pcs** pack.





Ionicore Membrane USmotric

TFC 2012 - **50** GPD
TFC 2012 - **75** GPD
TFC 2012 - **100** GPD
TFC 2012 - **150** GPD
TFC 2012 - **180** GPD

WATER COOLERS Accessories

	Ionicore IC-10SE Sediment in line filter 1/4" FPT 2"x10" 5 micron		Ionicore IC-11SE Sediment in line filter 1/4" FPT 2,5"x11" 5 micron		Ionicore IC-10CCB Coconut Carbon Block in line filter 1/4" FPT 2"x10" 10 micron		Ionicore IC-10CGAC Coconut granular activated carbon in line filter 1/4" NPT - 2"x10"
	Ionicore IC-11CGAC Coconut granular activated carbon in line filter 1/4" NPT - 2,5"x11"		Ionicore IC-11SCCB Silver coconut carbon block in line filter 1/4" NPT - 2,5"x11" 5 micron		Ionicore UF-11 / HF-PSU Ultrafiltration 1/4" FPT Ø stem 2,5"x11" 0,01 micron		Everpure QL2B Replacement single filter head 3/8" NPT
	Everpure Kit installation Assembled Kit IN-OUT 1/4"-1/4" wall plug 3/8"		Everpure AC2 Antimicrobial replacement filter 5.678lt. - 1,9lt./min. 0,2 micron		Everpure 4C2 Antimicrobial replacement filter 14.952lt. - 1,9lt./min. 0,2 micron		Everpure AC Replacement filter 2.840lt. - 1,9lt./min. 0,5 micron
	Everpure 4C Replacement filter 11.350lt. - 1,9lt./min. 0,5 micron		Everpure MC2 Antimicrobial replacement filter 34.000lt. - 6,3lt./min. 0,5 micron		System QL2B/UV System digital water counter with out Everpure cartridge		System QL2B/UV System auto-block water counter with out Everpure cartridge
	Filter head Profine S Replacement single filter head 8, 10mm., 1/4", 3/8" quick fit.		Profine SILVER mini Antimicrobial replacement filter 7.000lt. - 2,2lt./min 0,5 micron		Profine SILVER small Antimicrobial replacement filter 10.000lt. - 3lt./min 0,5 micron		Profine SILVER medium Antimicrobial replacement filter 15.000lt. - 5lt./min 0,5 micron
	Profine SILVER large Antimicrobial replacement filter 45.000lt. - 7lt./min 0,5 micron		Ranco thermostat K50-H2005-001 for ice bank, spiral probe (including fixing bracket, knob and plate)		Ranco thermostat K50.S.3485 for dry exchangers or storage (including fixing bracket, knob and plate)		Pico pump / agitator 400lt./h.

WATER COOLERS Accessories

	Water dispenser faucet Blue or red 3/8"		Pentek GS-10 in line filter CAL/RO -Remineralizer PH adjustment coconut (GAC) 1/4" FPT 2"x10" 20 micron		Green Filter in line filter Remineralizer PH adjustment coconut (GAC) 1/4" FPT - 2"x10"		Round drip Trays Drip trays for beer and beverage tapping systems. Materials: brass and stainless steel.
	Counter support for column with drip trays Materials: polished brass plated		Drip Trays Drip trays for beer and beverage tapping systems. Materials: brass and stainless steel.		Rounded drip Trays Drip trays for beer and beverage tapping systems. Materials: brass and stainless steel.		Balance 3-way column with handles 3 handles and ceramic headwork (cold water, sparkling, natural)
	Ice 1, 2, 3-way mechanical font Finishing available: chrome, gold plated. Materials used: brass		Osaka Faucet 2-way 1/4"		2008 Faucet with 2 star handles 2-way 1/4"		Long reach Faucet 3-way 6mm.
	3031 Faucet 3-way 6mm.		3033 Faucet 3-way 6mm.		3034 Faucet 3-way 6mm.		3023 Faucet 3-way 3/8"
	3024 Faucet 3-way 3/8"		3025 Faucet 3-way 3/8"		3036 Faucet 3-way 3/8"		Forum Faucet metal free 3-way 3/8"
	4006 Faucet 4-way 3/8"		4007 Faucet 4-way 3/8"		5015 Faucet 2-way 3/8" 3-way 6mm.		5019 Faucet 2-way 3/8" 3-way 6mm.



Distributor



Ver. 1.1