

## Features:

Rated voltage: 220V/50Hz

Rated power: 1700W

Heating power: 1500W

Cooling power: 170W

Cold water tank: 8ltr.

Hot water tank: 5ltr.

Sparkling water tank: 2ltr.

Cold water production: 6ltr./h. ( $\leq 10^{\circ}\text{C}$ )

Hot water production: 13,5ltr./h. ( $\geq 88^{\circ}\text{C}$ )

Sparkling water production: 6ltr./h.

Hot water temperature:  $\geq 88^{\circ}\text{C}$

Cold water temperature:  $\leq 10^{\circ}\text{C}$

Refrigerant: R600a

CO<sub>2</sub> gas capacity:  $\geq 3$  gr./ltr.

CO<sub>2</sub> inlet type: Food Grade Additive - Carbon Dioxide

CO<sub>2</sub> inlet pressure: 0,8MPa

Climate type: Temperate

Refrigerant fill: 18gr.

Water supply: Municipal

Feed water pressure: 0,1~0,3MPa

Operating pressure: 0,4~0,8MPa

Feed water temperature: 1~39°C

Filtered water flow:  $\geq 0,5$  ltr./min

Rated treated water capacity: 4000ltr.

Safety valve pressure: 0,95MPa

Recovery:  $\geq 45\%$

Appliance protection rating: Class I

Weight: 35kg.

Dimensions: 400x425x1400mm.

Distributed by:

CE

## 2, 3-way

### Reverse Osmosis Professional Dispenser

The **premium** solution for offices,  
hotels, restaurants, bars and gyms



Cold water • sparkling cold • hot



**Adjustable** professional carbonation



4-stage purification system:  
**PP + CTO + RO Membrane + CTO**



**Continuous flow dispensing:**  
up to 1,6 ltr. of sparkling water  
in just **15 seconds**



**Integrated UVC LED sterilization**  
with bactericidal function



**Reduction of costs and plastic**



6-13,5 ltr./h.



8 languages display



Acqua fredda  
Cold water  
Kaltes Wasser  
Agua fría  
Eau froide  
Κρύο νερό  
Холодная вода  
در آب عام



Acqua fredda frizzante  
Sparkling cold water  
Kaltes Sprudelwasser  
Agua fría con gas  
Eau froide pétillante  
Κρύο ανθρακούχο νερό  
Холодная вода с газом  
راوقل در ابل عاملا

Plastic bottles saved

NO PLASTIC

+/- Co2



TDS IN

TDS OUT



PPM

Water temperature



Acqua calda  
Hot water  
Heißes Wasser  
Agua caliente  
Eau chaude  
Ζεστό νερό  
Горячая вода  
نخاسل عاملا



Sbloccare  
Unlock  
Freischalten  
Desbloquear  
Ouvrir  
Ξεκλειδώνω  
Разблокировать  
حتف

Co2 empty

Filter element status indicator



Commercial-grade continuous high flow

2ltr. sparkling water tank  
One-time output of sparkling water 1,6ltr.  
Water production only takes 15 seconds



Powerful compressor cooling

8ltr. ice tank  
Ice water as low as 3°C  
R600a refrigerant  
Built-in evaporator

Automatic sparkling water concentration adjustment

Multi-level setting  
Digital pressure sensor (±3,6 PSI, millisecond-level)  
Real-time concentration display



Active and passive safety protection

High-precision pressure sensor  
Inlet pressure reducing valve  
Mechanical safety valve  
1.5mm high-strength bubble canister

